



DigiFort® wall media P300

Paper backed commercial wallcovering product sheet

General description:

Paper backed vinyl wallcovering suitable for ink jet printing

Roll specifications:

Width:	130	cm.
Length:	50	lm.
Internal core diameter	7,6	cm
Packaging	In Kraft paper with* or without cardboard box	
* with surcharge		

Composition:

Substrate weight:	90 ± 15 g/m ²	EN ISO 2286-2
Vinyl weight	210 ± 15 g/m ²	EN ISO 2286-2
Total weight	300 ± 15 g/m ²	EN ISO 2286-2
Thickness	* mm	EN ISO 2286-3

* Depends on embossing / structure

Printing inks:

Suitable for Solvent, Eco Solvent. Latex and UV-curable

Properties:

Coating Specially formulated acrylic laquer with exclusive ink jet properties.

Washability prior to printing:

Scrubable EN 259 –2

In general; Digitally printed wallcovering can be washed. Slight or moderate soiling can be removed using a combination of mild detergent and a damp cloth. Dabbing – certainly not rubbing is recommended to lift the soil. It is important to rinse off with clean water (absorbent) cloth washing in a low to high vertical action to prevent moisture at skirting level. Bleach, abrasive cleaners and similar compounds must not be used.

Resistance to chemicals prior to printing:

Resistant to: Soap; Detergents; Alcohol; Ammonia; Alkali; Diluted Acids.
Not resistant to: Solvents like Ketones; Esters; Aromatic hydrocarbons.

Installation:

Refer to installation recommendations leaflet inside the core of each roll.

Adhesives:

Heavy duty wallcovering adhesive BK 10 (manual) or BK 23 (industrial), or similar PVA substitute.

Safety/Ecological:

The material is classified as non-hazardous DIN 52900 or 91/155/EEG,2001/58/EC

Fire resistance:

Fire rating

Euro class	B s2d0
Class 0 / 1	BS 476 part 6/7
M1	NF P 92501 / 92507
B1	DIN 4102 – 01 *
* ABP Number : P-MPA-E-00-626	

Lightfastness:

7 out of 8 International Woolscale BS EN 20105 / ISO 105-B02