

FOREVER GmbH Robert-Bosch-Str. 43, 68542 Heddesheim

Transfer Instructions for printing:

FOREVER Waterslide HT

for application onto colored Candles, Ceramic & Glass

1 & 2-PAPER-SYSTEM
FOR LED-PRINTERS WITH & WITHOUT WHITE TONER



PRINT SETTINGS: CMYW PRINTERS

Paper Setting: Labels 1

• Paper Feeding: Multi-Purpose Tray

Image Mode: Mirrored



PRINT SETTINGS: CMYK PRINTERS

Paper Setting: Labels 1

Paper Feeding: Multi-Purpose TrayImage Mode: NOT Mirrored



HEAT PRESS SETTINGS:

	AUTOMATIC HEAT PRESSE	MANUAL HEAT PRESSE
PRESSURE	2 bar/29 psi	medium
TEMPERATURE	180°C/352°F	180°C/352°F
TIME	15-20 seconds	15-20 seconds





TRANSFER APPLICATION: CMYW PRINTERS

- **Pre-Heat** your Press until the lower plate is **HOT**.
- Print the picture in mirror image onto the FOREVER Laser-Dark (No-Cut) A-Paper.
- Place the Waterslide paper on top of the lower plate and place the A-Paper on the top of the Waterslide paper.
- Cover with a sheet of Matt Finishing Economy.
- Press together at 180°C/352°F with 2 bar/29 psi (medium pressure) for 15 20 seconds.
- **Separate** the Waterslide paper from the A-Paper after it is ABSOLUTELY COLD.
- Cut around the transfer as exactly as possible.
- Place the transfer in water for 30 seconds (The paper will roll up).
- Rub it carefully between the fingers in order to remove the carrier tape.
- Position the transfer onto the application and remove any air bubbles (Use your fingers or a Squeegee).
- Remove leftover water before allowing it to dry for 3 hours.





TRANSFER APPLICATION: CMYK PRINTERS

- Print the unmirrored picture onto the glossy side of the Waterslide HT paper.
- Cut around the picture as exactly as possible.
- Place the transfer in water for 30 seconds (The paper will roll up).
- **Rub** it carefully between the fingers in order to remove the carrier tape.
- Position the transfer onto the application and remove any air bubbles (Use your fingers or a Squeegee).
- Remove leftover water before allowing it to dry for 3 hours.